

# NANOISOLA Data Sheet

## NANOISOLA Waterproofing

<b>Product Name</b>	NANOISOLA Waterproofing
<b>INGREDIENT</b>	MODIFIED STYRENE – ACRYLIC – COPOLYMER - % 30.0 – 50.0 TITANIUM DIOXIDE - % 5.0 – 10.0 INSULATING NANO COMPOSITE MATERIAL - % 5.0 – 10.0 BUTYL GLYCOL ACCETATE 0.5 - 2 %
<b>Available Sizes</b>	5-gallon pail, larger sizes available
<b>Color</b>	White - It can be tinted to any color
<b>Environmental</b>	Eco friendly, Water based <b>No</b> Odor
<b>Shelf Life</b>	1 years after manufacture
<b>Storage Temperatures</b>	10°C to 35°C
<b>Coverage (r coats)</b>	Approx. 40 square meter per 5-gallon pail
<b>Material Applied to</b>	asphalt, wood, clay, cement tile, galvanized & metal surfaces, concrete & cement surfaces, swimming pools, etc.
<b>Product Attributes</b>	Energy savings, Waterproofing, mold & fungi resistance
<b>Certification</b>	Energy saving, Waterproofing, UV resistance, Mold & Fungi resistance, Adhesion and Permeability test - passed
<b>Application</b>	
Insulation and waterproofing. Residential and commercial applications up used for asphalt, wood, clay, cement tile, galvanized & metal surfaces, concrete & cement surfaces, swimming pools, and any other surfaces requiring insulation and water resistance. Product can be in a submerged environment. Can be used around steam and high humidity environments. Interior or exterior use.	
<b>Application Method</b>	
Surface must be clean and dry and free of grease, dirt solvents, etc. Apply directly to the surface. Each coat should be applied 200 microns in thickness with 3 hours dry time between coats. Application temperature range: 15°C to 50°C	
<b>Suggested Application Equipment</b>	
Airless sprayer, Paint sprayer, Brush or roller	

[www.nanoisola.com](http://www.nanoisola.com)