



## Selection & Specification Data

<b>Product Name</b>	NANOISOLA Residential
<b>Product No.</b>	0864400606150002
<b>Description</b>	<p>NANOISOLA is an Energy Saving Paint that has unique insulating properties, which will reduce heat loss through walls and ceilings.</p> <p>The insulating properties within NANOISOLA Paint form a thermally efficient barrier, considerably reducing heat loss. It will help increase room temperature in winter, and keeps it cooler in summer and allows walls to breathe easier.</p>
<b>Features</b>	<p>Reduces heat loss          Helps reduce your energy consumption          Very LOW VOC levels          Reduces condensation problems.          Extremely simple to use          Easily applied (Roller, Brush, Sprayer)          Strong resistance to Fungi &amp; Mold          UV Resistance          Translucent paint is also available</p>
<b>Base</b>	Water-based Acrylic Insulation Coating
<b>Gloss</b>	Flat
<b>Color</b>	Clear, semi-gloss - White, semi-gloss
<b>Product Attributes</b>	Thermal insulation, Mold & Fungi resistance, UV resistance
<b>Environmental</b>	Eco friendly, Water based No Odor
<b>Material Applied to</b>	Drywall, pre-painted walls, ceilings, wood, plastic, cement, stucco, fiberglass, metal substrates, other surfaces
<b>Coverage (3 coats)</b>	Approx. 10 square meter per gallon
<b>Viscosity</b>	3500 to 4000 (cps)
<b>VOC content</b>	100 g/L (calculated)
<b>Volume Solids</b>	40.0 (+ or - 2%)

## Substrates & Surface Protection

Surface must be clean and dry and free of grease, dirt solvents, etc.

Apply directly to the surface.

Each coat should be applied 70 microns in thickness with 8 hours dry time between each coat.

Three coats is the recommended minimum coverage.

Application temperature range: 15°C to 70°C

Remove all loose contamination by wire brushing.

Remove all dirt, grease, oil, soluble salts and other contaminations.

Remove all loose, flaking rust and/or paint by one of the following methods, if unable to sandblast use **St 3**

Power Tool Cleaning. If able to sandblast use **Sa 2.5**

Blast Cleaning.

## Application

Insulation and mold resistance.

Residential and commercial applications up used for drywall, pre-painted walls, wood, plastic, glass, cement, fiberglass, and any other surfaces requiring insulation and mold resistance.

Not for underwater use - product cannot be in a submerged environment.

Can be used around steam and high humidity environments

Interior or Exterior use

## Application Equipment

Nanolsola coatings can be applied with standard paint spray equipment. Equipment size and performance varies widely, so it is our intention to provide the following recommendations for various sizes of equipment which may be used for the coatings, in addition to other important items to ensure proper application.

- 1- Airless or H.V.L.P. sprayer to apply Nanolsola paint
- 2- Roller
- 3- Brush

Mixing by hand or slow speed mixer recommended before use.

## Product Data

Item	Metric Value	Test Method
UV-A Exposure	Excellent 2000 hrs	ASTM D-5894
Humidity Cabinet	Excellent 2000 hrs	ASTM D-4585
Permeability	5 perms/inch @ 23 deg C	ASTM 1653-03
Cross Hatch Adhesion	100% 5B	ASTM D-3359
Pull Apart Strength	2000-2100 psi	ASTM D-4541
Thermal Conductivity	(0.075 W/m/K)	Thermal Probe Study
Transmittance	0.00	Calculated
Flame Spread	Class A	ASTM E-84/87
Smoke Developed	Class A	ASTM E-84/87
Cyclic Salt Fog	Excellent 2000 hrs	ASTM B-117
Mold Resistance	Zero or minimal growth	ASTM G21

## Mixing & Thinning

<b>Mixing</b>	Care should be taken during mixing prior to application not to cause particle shear of the nanocomposite. Preferred method of mixing is using a mixing paddle at slow speed for approximately 2 minutes.
<b>Thinning</b>	Thinning is normally not needed
<b>Tinting</b>	NANOISOLA White Can be tinted with universal paint pigment

## Cleanup & Safety

<b>Cleanup</b>	Equipment may be cleaned with soap & water
<b>Safety</b>	Eye protection recommended
<b>Ventilation</b>	Recommended for constricted areas
<b>Caution</b>	This material is not for human consumption
<b>Clothing</b>	Safety clothing & gloves are recommended

## Other Coating Specifications

<b>Thickness of 1 coat</b>	70 microns
<b>Thickness of 3 coat</b>	200 microns
<b>Touch dry time for 1 coat</b>	1 hour
<b>Typical hard dry time</b>	72 hours
<b>Dry time between each coat</b>	8 hours

## Package, Handling & Storage

<b>Available Sizes</b>	1-gallon & 5-gallon
<b>Shelf Life</b>	2 years after manufacture
<b>Storage Temperatures</b>	10°C to 35°C
<b>Caution</b>	Do not let product freeze
<b>Flash Point</b>	None
<b>Pot life</b>	Coating is one part, so no catalyzation is needed. Pail can be reused if properly sealed.

**Nanolsola** is a unique nanotechnology-based coating that insulates by reducing direct thermal conduction, NOT only by reflecting away the sun's heat but also makes them extremely effective in indoor as well as outdoor environments and in all climates and all seasons.

**Nanolsola** Coatings ARE NOT Ceramic paint additives Nor Microsphere coatings.

Nanofan Industrial Coatings LLC

Unit 3, Plot No.3390, Sohar free zone,  
Sohar, Sultanate of Oman  
Tel: +968 24 273739

Email: [oman@nanofanco.com](mailto:oman@nanofanco.com)

[www.nanolsola.com](http://www.nanolsola.com)

