



The application of Intelligence to Industry based upon Integrity




Exclusive manufacturer of Nano Insulation Paint in the Middle East.

NANOISOLA Residential – Interior & Exterior

- ✓ Commercial
- ✓ Residential
- ✓ Industrial
- ✓ Interior Walls
- ✓ Exterior Walls
- ✓ Ceilings
- ✓ Attics
- ✓ Basements
- ✓ Roofs
- ✓ Mobile Homes
- ✓ Sheds
- ✓ Metal Buildings



BRUSH



ROLLER



SPRAYER



Application Method

- ✓ Surface must be clean and dry and free of grease, dirt solvents, etc.
- ✓ Three coats is the recommended minimum coverage for insulation purposes.
- ✓ Each coat should be applied 70 microns in thickness with 8 hours dry time between each coat.
- ✓ Coverage rate: approximately 15 sq if applied in 3 coats.
- ✓ Apply with: Brush, Roller, Sprayer.



BRUSH



ROLLER



SPRAYER

Application Method



NANOISOLA Clear

Gallon

Coverage: 10 m²

5 Gallon pail

Coverage: 50 m²

Thickness: 0.2 mm with 3-coats



NANOISOLA Clear

Gallon

Coverage: 10 m²

5 Gallon pail

Coverage: 50 m²

Thickness: 0.2 mm with 3-coats

NANOISOLA Residential - Exterior Use



NANOISOLA Residential - Interior Use



More Information



Nanofan Industrial Coatings LLC

Unit A8, Plot No.3390, Sohar free zone,

Sohar, Sultanate of Oman

Phone: +968 2427 3739, GSM: +968 9099 6490

Email: oman@nanofanco.com www.nanofanco.com